

FRAME SPECIFICATIONS

All frames have a 68mm bottom bracket shell and they all use a 27.2 seatpost.

ANGUS

Size	S/T C-C	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	C/S Length	Stand Over
50cm	46 cm	52cm	72.0°	75.0°	10 cm	95 cm	5 cm	39.1 cm	29.5"
53cm	49 cm	54 cm	72.0°	73.0°	10 cm	95.7 cm	5 cm	39.1 cm	30"
56cm	52 cm	55.5 cm	73.0°	73.0°	12.5 cm	96 cm	5 cm	39.1 cm	31"
59cm	55 cm	57 cm	74.0°	73.0°	15 cm	96.6 cm	5 cm	39.1 cm	32"
62cm	58 cm	59 cm	75.0°	73.0°	17.8 cm	97.5 cm	5 cm	39.1 cm	33.5"

Rear Dropout 120mm

JAMIE ROY

Size	S/T C-C	T/T Effective	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	C/S Length	Stand Over
50cm	46 cm	54.5 cm	53cm	72.5°	73.5°	11 cm	98.6 cm	7 cm	41.5 cm	29.5"
53cm	49 cm	55 cm	54.7 cm	72.5°	73.5°	13 cm	100 cm	7 cm	41.5 cm	30"
56cm	52 cm	57.5 cm	56.5 cm	73.0°	73.0°	15 cm	101 cm	7 cm	41.5 cm	31"
59cm	55 cm	59 cm	58.3 cm	73.0°	73.0°	17 cm	102.5 cm	7 cm	41.5 cm	32"
62cm	58 cm	60.5 cm	60 cm	73.0°	73.0°	19 cm	103.9 cm	7 cm	41.5 cm	32.5"

Rear Dropout 130mm

ROB ROY - DISCONTINUED

Size	S/T C-C	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	C/S Length	Stand Over
50cm	46 cm	53 cm	72.5°	73.5°	10 cm	101 cm	6.5 cm	42.5 cm	29.5"
53cm	50 cm	54 cm	72.5°	73.5°	11.5 cm	102 cm	6.5 cm	42.5 cm	30.5"
56cm	52 cm	55 cm	73.0°	73.0°	13 cm	103 cm	6.5 cm	42.5 cm	31"
59cm	54 cm	56 cm	73.0°	73.0°	15 cm	104 cm	6.5 cm	42.5 cm	32"
62cm	56 cm	57 cm	73.0°	73.0°	17 cm	105 cm	6.5 cm	42.5 cm	32.5"

Rear Dropout 130mm

FRAME SPECIFICATIONS

MODEL 19

Size	S/T C-C	T/T Effective	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	Stand Over
16"	16"	24"	23.1"	72.0°	73.0°	3.5"	42.5"	2.75"	29"
18"	18"	24.65"	23.6"	72.0°	73.0°	4"	43"	2.75"	30.5"
20"	20.4"	25.25"	24.3"	72.0°	73.0°	4.3"	43.7"	2.75"	32"
22"	22"	25.85"	25"	72.0°	73.0°	4.7"	44.25"	2.75"	33"

Rear Dropout 135mm

THE PHOENIX

Size	S/T C-C	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	C/S Length	Stand Over
50cm	45.5 cm	52 cm	72.0°	73.5°	8.5 cm	101 cm	6.5 cm	42.5	29.5"
52cm	47.5 cm	53 cm	72.0°	73.5°	8.5 cm	101.5 cm	6.5 cm	42.5	30"
54cm	49.5 cm	54 cm	72.0°	73.5°	9.2 cm	102 cm	6.5 cm	42.5	30.5"
56cm	51.5 cm	55 cm	72.0°	73.0°	10.5 cm	103 cm	6.5 cm	42.5	31.5"
58cm	53.5 cm	56 cm	72.0°	73.0°	12.5 cm	104 cm	6.5 cm	42.5	32"
60cm	55.5 cm	57 cm	72.0°	73.0°	14.5 cm	105 cm	6.5 cm	42.5	33"

Rear Dropout 120mm

MARK V

Size	S/T C-C	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	C/S Length	Stand Over
50cm	46 cm	52 cm	72.0°	75.0°	10 cm	95 cm	5 cm	39.1 cm	29.5"
53cm	49 cm	54 cm	72.0°	73.0°	10 cm	95.7 cm	5 cm	39.1 cm	30"
56cm	52 cm	55.5 cm	73.0°	73.0°	12.5 cm	96 cm	5 cm	39.1 cm	31"
59cm	55 cm	57 cm	74.0°	73.0°	15 cm	96.6 cm	5 cm	39.1 cm	32"
62cm	56 cm	59 cm	75.0°	73.0°	17.8 cm	97.5 cm	5 cm	39.1 cm	33.5"

Rear Dropout 120mm

FRAME SPECIFICATIONS

MARK V PRO

Size	S/T C-C	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	C/S Length	Stand Over
50cm	46 cm	52 cm	72.0°	75.0°	10 cm	95 cm	5 cm	39.1 cm	29.5"
53cm	49 cm	54 cm	72.0°	73.0°	10 cm	95.7 cm	5 cm	39.1 cm	30"
56cm	52 cm	55.5 cm	73.0°	73.0°	12.5 cm	96 cm	5 cm	39.1 cm	31"
59cm	55 cm	57 cm	74.0°	73.0°	15 cm	96.6 cm	5 cm	39.1 cm	32"
62cm	56 cm	59 cm	75.0°	73.0°	17.8 cm	97.5 cm	5 cm	39.1 cm	33.5"

Rear Dropout 120mm

THE HEIDI/MARK V HD

Size	S/T C-C	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	C/S Length	Stand Over
46cm	42 cm	50 cm	73.5°	74.5°	9 cm	90 cm	5 cm	36 cm	27"

Rear Dropout 120mm
Wheels 650C

THE DABU

Size	S/T C-C	T/T Length	H/T Angle	S/T Angle	H/T Length	B/B Drop	C/S Length
20.25in	25.3 cm	51.4 cm	75°	71°	11.7 cm	3.2 cm	35.5 cm
21.25cm	25.3 cm	53.9 cm	75°	71°	11.7 cm	3.2 cm	35.5 cm

Rear Dropout 110mm

FRAME SPECIFICATIONS

THE WTF

Size	S/T C-C	T/T Length	H/T Angle	S/T Angle	H/T Length	Wheel Base	B/B Drop	C/S Length	Stand Over
50cm	45.5 cm	52 cm	72.0°	73.5°	8.5 cm	101 cm	6.5 cm	42.5	29.5"
52cm	47.5 cm	53 cm	72.0°	73.5°	8.5 cm	101.5 cm	6.5 cm	42.5	30"
54cm	49.5 cm	54 cm	72.0°	73.5°	9.2 cm	102 cm	6.5 cm	42.5	30.5"
56cm	51.5 cm	55 cm	72.0°	73.0°	10.5 cm	103 cm	6.5 cm	42.5	31.5"
58cm	53.5 cm	56 cm	72.0°	73.0°	12.5 cm	104 cm	6.5 cm	42.5	32"
60cm	55.5 cm	57 cm	72.0°	73.0°	14.5 cm	105 cm	6.5 cm	42.5	33"

Rear Dropout 120mm

HUB SPECIFICATIONS

HIGH FLANGE TRACK HUBS	LOW FLANGE FIXED/FREE HUBS
Front Width from center to flange 34.5 mm Flange diameter 62.0 mm Rear Width from center to flange 31.0 mm Flange diameter 62.0 mm Chain Line 42 mm Weight Front: 271g, Rear 324g	Front Width from center to flange 34.5 mm Flange diameter 37.5 mm Rear Width from center to flange 31.0 mm Flange diameter 42.0 mm Chain Line 42 mm Weight Front: 213g, Rear 290g

RIM SPECIFICATIONS

COLD FUSION RIMS

Size	Bead Seat Diameter	Weight	ERD
650c	571	465g	541
700c	622	475g	591